

Cross Reference To Related Application

A1 5-29-2
This is a continuation of Application No. 09/302,259 filed April 30, 1999,
now Patent No. 6,289,650
(Confirmation No. unknown), the entire disclosure of which is incorporated
herein by reference.

Page 1, replace the 1st paragraph as follows:

A2
The present invention relates to an automatic plate making machine equipped with a photosensitive printing plate supplying apparatus and photosensitive printing plate packaging means. In the photosensitive printing plate supplying apparatus, photosensitive printing plates packaged in the printing plate packaging means are first taken out therefrom in a condition in which light from the outside is blocked, and the photosensitive printing plates which have been taken out are conveyed to a predetermined position in an automatic plate making machine or the like by the same supplying apparatus. The photosensitive printing plate packaging means is designed such that taking out the photosensitive printing plates from the packaging means by the photosensitive printing plate supplying apparatus can be carried out in an optimum way inside the same supplying apparatus.

Pages 9-10, replace the bridging paragraph as follows:

A3
F03030: E2 F03030
In accordance with the second aspect, when the above-described photo-sensitive printing plate packaging means is attached to the printing plate accommodating portion in the printing plate supplying apparatus, the lid opening/closing means moves the opening/closing lid to an opening position or a closing position in the light-shielded chamber and thus the supply opening of the printing plate packaging box can be opened/closed. Also, in accordance with the second aspect, since the opening/closing lid removably covers the box, when the supply opening is to be opened, the lid opening/closing means moves the opening/closing lid to the opening position which removes the opening/closing lid from the box, and when the supply opening is to be closed, the lid opening/closing means moves the opening/closing lid at the opening position to the closing position in which the opening/closing lid covers the box.

Page 10, replace the 2nd full paragraph as follows:

A4
In accordance with the third aspect, when the above-described photo-sensitive printing plate packaging means is attached to the printing plate accommodating portion in the printing plate supplying apparatus, the lid opening/closing means moves the lid portion to an opening position or a closing position in the light-shielded chamber and thus the supply opening of

A4 the printing plate packaging box can be opened/closed. Also, in accordance with the third aspect, since the lid portion is swingably supported by the box, the lid opening/closing means swings the lid portion to the opening position or the closing position.

Pages 10-11, replace the bridging paragraph as follows:

A5
10330-47600
A fourth aspect of the present invention is an automatic plate making machine for a photosensitive printing plate, wherein the printing plate packaging means includes a box main body, which is formed in a box shape such that the bundle of photosensitive printing plates can be accommodated therein and which is provided with the supply opening through which the photosensitive printing plates are taken out, and an opening/closing lid which can be slidably attached to the box for opening/closing the supply opening.

Page 11, replace the 1st full paragraph as follows:

A6 In accordance with the fourth aspect of the present invention, when the above-described photosensitive printing plate packaging means is attached to the printing plate accommodating portion in the printing plate supplying apparatus, the lid opening/closing means moves the opening/closing lid to an

A6 opening position or a closing position in the light-shielded chamber and thus the supply opening of the printing plate packaging box can be opened/closed. Also, in accordance with the fourth aspect, since the opening/closing lid is slidably supported by the box, the lid opening/closing means slides the opening/closing lid to the opening position or the closing position.

Page 14, replace the 1st and 2nd paragraphs as follows:

A7 When this pulling-out force reaches a predetermined value, the packaging means main body breaks and at least a portion of the packaged photosensitive printing plate packaged therein is made exposed. The photosensitive printing plate supplying apparatus can now convey the photosensitive printing plate to the starting position of plate making of the automatic plate making machine. Further, as the photosensitive printing plates made exposed by losing the packaging means main body is still completely shielded from light by the photosensitive printing plate supplying apparatus, the photosensitive printing plate can reliably avoid being subject to accidental exposure.

Accordingly, since the photosensitive printing plate is always loaded into the photosensitive printing plate supplying apparatus in a state in which the photosensitive printing plate is light-shielded by the packaging means main body, the loading operation can be carried out even under the bright

A7 environment. Therefore, the operational efficiency improves as compared to the conventional example in which the loading operation is effected under the dark environment, and the operator's burden is significantly reduced.

Pages 32-33, replace the bridging paragraph as follows:

AB 03080-22600
sub The opening/closing lid 48 is formed so that the depth thereof is smaller than that of the box main body 46. When the opening/closing lid 48 covers the box main body 46, the lower end portions of the side plate portions 46B and 46C of the box main body 46 are exposed to the exterior. Therefore, when the printing plate packaging box 28 is attached to the mounting surface 30, the positioning plates 32 and 34 abut only the lower end portions of the side plate portions 46B and 46C (that is, not abutting the side plate portions 48B and 48C located outside of the side plate portions 46B and 46C) when these positioning plates 32 and 34 position the printing plate packaging box 28 at a predetermined reference position. Accordingly, since the positioning plates 32 and 34 are prevented from contacting the opening/closing lid 48, the opening/closing lid 48 can be opened and closed without being interfered with by the positioning plates 32 and 34.

Pages 35-36, replace the bridging paragraph as follows:

A9
The guide rail 58 extends in the direction normal to the mounting surface 30 of the printing plate supplying cassette 18. The drive portion 60 is provided with a drive motor (not shown), a drive roller 64 which is normally and reversely rotated by this drive motor, and idle rollers 66 which sandwich the guide rail 58 with this drive roller 64 as shown. When the drive roller 64 of the drive portion 60 is rotated normally or reversely, the drive portion 60 moves in the direction of moving closer to or away from the printing plate packaging box 28 on the mounting surface 30. Further, an air suction pump 68 is provided in the drive portion 60.

Page 37, replace the 1st full paragraph as follows:

A10
The drive portion 80 is provided with a drive motor (not shown), a drive roller 84 which is normally and reversely rotated by this drive motor, and idle rollers 86 which sandwich the guide rail 78 with this drive roller 84 as shown. When the drive roller 84 of the drive portion 80 is rotated normally or reversely, the drive portion 80 moves in the lower end direction or the upper end direction of the guide rail 78.

Page 75, replace the 1st full paragraph as follows:

Next, the adhesive tape 418D at the long edge 414B side which is disposed at the upper portion in Fig. 17 and the adhesive tape 418B at the center (see Fig. 14) are peeled off. The folded portion 424 is then extended upwardly so that the portion 424 juts out of the photosensitive printing plate supplying apparatus 432 as shown in Fig. 17. In this way, the folded portion 424 serves as a jutting-out portion 420, and the rest of the packaging paper 410 serves as a packaging means main body. Then, the slide door 440 is slid upwardly such that this jutting-out portion 420 is nipped between the upper edge of the slide door 440 and the cassette accommodating portion 434. The slide door 440 is locked at the completely closed position by the unillustrated lock device. In this way, the photosensitive printing plate 42 is doubly completely shielded from light by the packaging paper 410 and the photosensitive printing plate supplying apparatus 432.

Page 81, replace the 3rd full paragraph as follows:

Fig. 25 shows a packaging paper 650 which is a sixth embodiment of the present invention. Further, Fig. 26 shows this packaging paper 650 in an unfolded state. A display portion 622 is provided.

Page 85, replace the 3rd full paragraph as follows:

A13 Fig. 29 shows a state in which a packaging paper 780 in a seventh embodiment of the present invention packages the bundle 49 of the photo-sensitive printing plates 42. Further, Fig. 30 shows this packaging paper 780 in an unfolded state. A display portion 722 is provided.

Pages 86-87, replace the bridging paragraph as follows:

A14
FIG. 29-30
FIG. 31-32
FIG. 33-34
FIG. 35-36
FIG. 37-38
FIG. 39-40
FIG. 41-42
FIG. 43-44
FIG. 45-46
FIG. 47-48
FIG. 49-50
FIG. 51-52
FIG. 53-54
FIG. 55-56
FIG. 57-58
FIG. 59-60
FIG. 61-62
FIG. 63-64
FIG. 65-66
FIG. 67-68
FIG. 69-70
FIG. 71-72
FIG. 73-74
FIG. 75-76
FIG. 77-78
FIG. 79-80
FIG. 81-82
FIG. 83-84
FIG. 85-86
FIG. 87-88
FIG. 89-90
FIG. 91-92
FIG. 93-94
FIG. 95-96
FIG. 97-98
FIG. 99-100
FIG. 101-102
FIG. 103-104
FIG. 105-106
FIG. 107-108
FIG. 109-110
FIG. 111-112
FIG. 113-114
FIG. 115-116
FIG. 117-118
FIG. 119-120
FIG. 121-122
FIG. 123-124
FIG. 125-126
FIG. 127-128
FIG. 129-130
FIG. 131-132
FIG. 133-134
FIG. 135-136
FIG. 137-138
FIG. 139-140
FIG. 141-142
FIG. 143-144
FIG. 145-146
FIG. 147-148
FIG. 149-150
FIG. 151-152
FIG. 153-154
FIG. 155-156
FIG. 157-158
FIG. 159-160
FIG. 161-162
FIG. 163-164
FIG. 165-166
FIG. 167-168
FIG. 169-170
FIG. 171-172
FIG. 173-174
FIG. 175-176
FIG. 177-178
FIG. 179-180
FIG. 181-182
FIG. 183-184
FIG. 185-186
FIG. 187-188
FIG. 189-190
FIG. 191-192
FIG. 193-194
FIG. 195-196
FIG. 197-198
FIG. 199-200
FIG. 201-202
FIG. 203-204
FIG. 205-206
FIG. 207-208
FIG. 209-210
FIG. 211-212
FIG. 213-214
FIG. 215-216
FIG. 217-218
FIG. 219-220
FIG. 221-222
FIG. 223-224
FIG. 225-226
FIG. 227-228
FIG. 229-230
FIG. 231-232
FIG. 233-234
FIG. 235-236
FIG. 237-238
FIG. 239-240
FIG. 241-242
FIG. 243-244
FIG. 245-246
FIG. 247-248
FIG. 249-250
FIG. 251-252
FIG. 253-254
FIG. 255-256
FIG. 257-258
FIG. 259-260
FIG. 261-262
FIG. 263-264
FIG. 265-266
FIG. 267-268
FIG. 269-270
FIG. 271-272
FIG. 273-274
FIG. 275-276
FIG. 277-278
FIG. 279-280
FIG. 281-282
FIG. 283-284
FIG. 285-286
FIG. 287-288
FIG. 289-290
FIG. 291-292
FIG. 293-294
FIG. 295-296
FIG. 297-298
FIG. 299-300
FIG. 301-302
FIG. 303-304
FIG. 305-306
FIG. 307-308
FIG. 309-310
FIG. 311-312
FIG. 313-314
FIG. 315-316
FIG. 317-318
FIG. 319-320
FIG. 321-322
FIG. 323-324
FIG. 325-326
FIG. 327-328
FIG. 329-330
FIG. 331-332
FIG. 333-334
FIG. 335-336
FIG. 337-338
FIG. 339-340
FIG. 341-342
FIG. 343-344
FIG. 345-346
FIG. 347-348
FIG. 349-350
FIG. 351-352
FIG. 353-354
FIG. 355-356
FIG. 357-358
FIG. 359-360
FIG. 361-362
FIG. 363-364
FIG. 365-366
FIG. 367-368
FIG. 369-370
FIG. 371-372
FIG. 373-374
FIG. 375-376
FIG. 377-378
FIG. 379-380
FIG. 381-382
FIG. 383-384
FIG. 385-386
FIG. 387-388
FIG. 389-390
FIG. 391-392
FIG. 393-394
FIG. 395-396
FIG. 397-398
FIG. 399-400
FIG. 401-402
FIG. 403-404
FIG. 405-406
FIG. 407-408
FIG. 409-410
FIG. 411-412
FIG. 413-414
FIG. 415-416
FIG. 417-418
FIG. 419-420
FIG. 421-422
FIG. 423-424
FIG. 425-426
FIG. 427-428
FIG. 429-430
FIG. 431-432
FIG. 433-434
FIG. 435-436
FIG. 437-438
FIG. 439-440
FIG. 441-442
FIG. 443-444
FIG. 445-446
FIG. 447-448
FIG. 449-450
FIG. 451-452
FIG. 453-454
FIG. 455-456
FIG. 457-458
FIG. 459-460
FIG. 461-462
FIG. 463-464
FIG. 465-466
FIG. 467-468
FIG. 469-470
FIG. 471-472
FIG. 473-474
FIG. 475-476
FIG. 477-478
FIG. 479-480
FIG. 481-482
FIG. 483-484
FIG. 485-486
FIG. 487-488
FIG. 489-490
FIG. 491-492
FIG. 493-494
FIG. 495-496
FIG. 497-498
FIG. 499-500
FIG. 501-502
FIG. 503-504
FIG. 505-506
FIG. 507-508
FIG. 509-510
FIG. 511-512
FIG. 513-514
FIG. 515-516
FIG. 517-518
FIG. 519-520
FIG. 521-522
FIG. 523-524
FIG. 525-526
FIG. 527-528
FIG. 529-530
FIG. 531-532
FIG. 533-534
FIG. 535-536
FIG. 537-538
FIG. 539-540
FIG. 541-542
FIG. 543-544
FIG. 545-546
FIG. 547-548
FIG. 549-550
FIG. 551-552
FIG. 553-554
FIG. 555-556
FIG. 557-558
FIG. 559-560
FIG. 561-562
FIG. 563-564
FIG. 565-566
FIG. 567-568
FIG. 569-570
FIG. 571-572
FIG. 573-574
FIG. 575-576
FIG. 577-578
FIG. 579-580
FIG. 581-582
FIG. 583-584
FIG. 585-586
FIG. 587-588
FIG. 589-590
FIG. 591-592
FIG. 593-594
FIG. 595-596
FIG. 597-598
FIG. 599-600
FIG. 601-602
FIG. 603-604
FIG. 605-606
FIG. 607-608
FIG. 609-610
FIG. 611-612
FIG. 613-614
FIG. 615-616
FIG. 617-618
FIG. 619-620
FIG. 621-622
FIG. 623-624
FIG. 625-626
FIG. 627-628
FIG. 629-630
FIG. 631-632
FIG. 633-634
FIG. 635-636
FIG. 637-638
FIG. 639-640
FIG. 641-642
FIG. 643-644
FIG. 645-646
FIG. 647-648
FIG. 649-650
FIG. 651-652
FIG. 653-654
FIG. 655-656
FIG. 657-658
FIG. 659-660
FIG. 661-662
FIG. 663-664
FIG. 665-666
FIG. 667-668
FIG. 669-670
FIG. 671-672
FIG. 673-674
FIG. 675-676
FIG. 677-678
FIG. 679-680
FIG. 681-682
FIG. 683-684
FIG. 685-686
FIG. 687-688
FIG. 689-690
FIG. 691-692
FIG. 693-694
FIG. 695-696
FIG. 697-698
FIG. 699-700
FIG. 701-702
FIG. 703-704
FIG. 705-706
FIG. 707-708
FIG. 709-710
FIG. 711-712
FIG. 713-714
FIG. 715-716
FIG. 717-718
FIG. 719-720
FIG. 721-722
FIG. 723-724
FIG. 725-726
FIG. 727-728
FIG. 729-730
FIG. 731-732
FIG. 733-734
FIG. 735-736
FIG. 737-738
FIG. 739-740
FIG. 741-742
FIG. 743-744
FIG. 745-746
FIG. 747-748
FIG. 749-750
FIG. 751-752
FIG. 753-754
FIG. 755-756
FIG. 757-758
FIG. 759-760
FIG. 761-762
FIG. 763-764
FIG. 765-766
FIG. 767-768
FIG. 769-770
FIG. 771-772
FIG. 773-774
FIG. 775-776
FIG. 777-778
FIG. 779-780
FIG. 781-782
FIG. 783-784
FIG. 785-786
FIG. 787-788
FIG. 789-790
FIG. 791-792
FIG. 793-794
FIG. 795-796
FIG. 797-798
FIG. 799-800
FIG. 801-802
FIG. 803-804
FIG. 805-806
FIG. 807-808
FIG. 809-810
FIG. 811-812
FIG. 813-814
FIG. 815-816
FIG. 817-818
FIG. 819-820
FIG. 821-822
FIG. 823-824
FIG. 825-826
FIG. 827-828
FIG. 829-830
FIG. 831-832
FIG. 833-834
FIG. 835-836
FIG. 837-838
FIG. 839-840
FIG. 841-842
FIG. 843-844
FIG. 845-846
FIG. 847-848
FIG. 849-850
FIG. 851-852
FIG. 853-854
FIG. 855-856
FIG. 857-858
FIG. 859-860
FIG. 861-862
FIG. 863-864
FIG. 865-866
FIG. 867-868
FIG. 869-870
FIG. 871-872
FIG. 873-874
FIG. 875-876
FIG. 877-878
FIG. 879-880
FIG. 881-882
FIG. 883-884
FIG. 885-886
FIG. 887-888
FIG. 889-890
FIG. 891-892
FIG. 893-894
FIG. 895-896
FIG. 897-898
FIG. 899-900
FIG. 901-902
FIG. 903-904
FIG. 905-906
FIG. 907-908
FIG. 909-910
FIG. 911-912
FIG. 913-914
FIG. 915-916
FIG. 917-918
FIG. 919-920
FIG. 921-922
FIG. 923-924
FIG. 925-926
FIG. 927-928
FIG. 929-930
FIG. 931-932
FIG. 933-934
FIG. 935-936
FIG. 937-938
FIG. 939-940
FIG. 941-942
FIG. 943-944
FIG. 945-946
FIG. 947-948
FIG. 949-950
FIG. 951-952
FIG. 953-954
FIG. 955-956
FIG. 957-958
FIG. 959-960
FIG. 961-962
FIG. 963-964
FIG. 965-966
FIG. 967-968
FIG. 969-970
FIG. 971-972
FIG. 973-974
FIG. 975-976
FIG. 977-978
FIG. 979-980
FIG. 981-982
FIG. 983-984
FIG. 985-986
FIG. 987-988
FIG. 989-990
FIG. 991-992
FIG. 993-994
FIG. 995-996
FIG. 997-998
FIG. 999-1000
FIG. 1001-1002
FIG. 1003-1004
FIG. 1005-1006
FIG. 1007-1008
FIG. 1009-1010
FIG. 1011-1012
FIG. 1013-1014
FIG. 1015-1016
FIG. 1017-1018
FIG. 1019-1020
FIG. 1021-1022
FIG. 1023-1024
FIG. 1025-1026
FIG. 1027-1028
FIG. 1029-1030
FIG. 1031-1032
FIG. 1033-1034
FIG. 1035-1036
FIG. 1037-1038
FIG. 1039-1040
FIG. 1041-1042
FIG. 1043-1044
FIG. 1045-1046
FIG. 1047-1048
FIG. 1049-1050
FIG. 1051-1052
FIG. 1053-1054
FIG. 1055-1056
FIG. 1057-1058
FIG. 1059-1060
FIG. 1061-1062
FIG. 1063-1064
FIG. 1065-1066
FIG. 1067-1068
FIG. 1069-1070
FIG. 1071-1072
FIG. 1073-1074
FIG. 1075-1076
FIG. 1077-1078
FIG. 1079-1080
FIG. 1081-1082
FIG. 1083-1084
FIG. 1085-1086
FIG. 1087-1088
FIG. 1089-1090
FIG. 1091-1092
FIG. 1093-1094
FIG. 1095-1096
FIG. 1097-1098
FIG. 1099-1100
FIG. 1101-1102
FIG. 1103-1104
FIG. 1105-1106
FIG. 1107-1108
FIG. 1109-1110
FIG. 1111-1112
FIG. 1113-1114
FIG. 1115-1116
FIG. 1117-1118
FIG. 1119-1120
FIG. 1121-1122
FIG. 1123-1124
FIG. 1125-1126
FIG. 1127-1128
FIG. 1129-1130
FIG. 1131-1132
FIG. 1133-1134
FIG. 1135-1136
FIG. 1137-1138
FIG. 1139-1140
FIG. 1141-1142
FIG. 1143-1144
FIG. 1145-1146
FIG. 1147-1148
FIG. 1149-1150
FIG. 1151-1152
FIG. 1153-1154
FIG. 1155-1156
FIG. 1157-1158
FIG. 1159-1160
FIG. 1161-1162
FIG. 1163-1164
FIG. 1165-1166
FIG. 1167-1168
FIG. 1169-1170
FIG. 1171-1172
FIG. 1173-1174
FIG. 1175-1176
FIG. 1177-1178
FIG. 1179-1180
FIG. 1181-1182
FIG. 1183-1184
FIG. 1185-1186
FIG. 1187-1188
FIG. 1189-1190
FIG. 1191-1192
FIG. 1193-1194
FIG. 1195-1196
FIG. 1197-1198
FIG. 1199-1200
FIG. 1201-1202
FIG. 1203-1204
FIG. 1205-1206
FIG. 1207-1208
FIG. 1209-1210
FIG. 1211-1212
FIG. 1213-1214
FIG. 1215-1216
FIG. 1217-1218
FIG. 1219-1220
FIG. 1221-1222
FIG. 1223-1224
FIG. 1225-1226
FIG. 1227-1228
FIG. 1229-1230
FIG. 1231-1232
FIG. 1233-1234
FIG. 1235-1236
FIG. 1237-1238
FIG. 1239-1240
FIG. 1241-1242
FIG. 1243-1244
FIG. 1245-1246
FIG. 1247-1248
FIG. 1249-1250
FIG. 1251-1252
FIG. 1253-1254
FIG. 1255-1256
FIG. 1257-1258
FIG. 1259-1260
FIG. 1261-1262
FIG. 1263-1264
FIG. 1265-1266
FIG. 1267-1268
FIG. 1269-1270
FIG. 1271-1272
FIG. 1273-1274
FIG. 1275-1276
FIG. 1277-1278
FIG. 1279-1280
FIG. 1281-1282
FIG. 1283-1284
FIG. 1285-1286
FIG. 1287-1288
FIG. 1289-1290
FIG. 1291-1292
FIG. 1293-1294
FIG. 1295-1296
FIG. 1297-1298
FIG. 1299-1300
FIG. 1301-1302
FIG. 1303-1304
FIG. 1305-1306
FIG. 1307-1308
FIG. 1309-1310
FIG. 1311-1312
FIG. 1313-1314
FIG. 1315-1316
FIG. 1317-1318
FIG. 1319-1320
FIG. 1321-1322
FIG. 1323-1324
FIG. 1325-1326
FIG. 1327-1328
FIG. 1329-1330
FIG. 1331-1332
FIG. 1333-1334
FIG. 1335-1336
FIG. 1337-1338
FIG. 1339-1340
FIG. 1341-1342
FIG. 1343-1344
FIG. 1345-1346
FIG. 1347-1348
FIG. 1349-1350
FIG. 1351-1352
FIG. 1353-1354
FIG. 1355-1356
FIG. 1357-1358
FIG. 1359-1360
FIG. 1361-1362
FIG. 1363-1364
FIG. 1365-1366
FIG. 1367-1368
FIG. 1369-1370
FIG. 1371-1372
FIG. 1373-1374
FIG. 1375-1376
FIG. 1377-1378
FIG. 1379-1380
FIG. 1381-1382
FIG. 1383-1384
FIG. 1385-1386
FIG. 1387-1388
FIG. 1389-1390
FIG. 1391-1392
FIG. 1393-1394
FIG. 1395-1396
FIG. 1397-1398
FIG. 1399-1400
FIG. 1401-1402
FIG. 1403-1404
FIG. 1405-1406
FIG. 1407-1408
FIG. 1409-1410
FIG. 1411-1412
FIG. 1413-1414
FIG. 1415-1416
FIG. 1417-1418
FIG. 1419-1420
FIG. 1421-1422
FIG. 1423-1424
FIG. 1425-1426
FIG. 1427-1428
FIG. 1429-1430
FIG. 1431-1432
FIG. 1433-1434
FIG. 1435-1436
FIG. 1437-1438
FIG. 1439-1440
FIG. 1441-1442
FIG. 1443-1444
FIG. 1445-1446
FIG. 1447-1448
FIG. 1449-1450
FIG. 1451-1452
FIG. 1453-1454
FIG. 1455-1456
FIG. 1457-1458
FIG. 1459-1460
FIG. 1461-1462
FIG. 1463-1464
FIG. 1465-1466
FIG. 1467-1468
FIG. 1469-1470
FIG. 1471-1472
FIG. 1473-1474
FIG. 1475-1476
FIG. 1477-1478
FIG. 1479-1480
FIG. 1481-1482
FIG. 1483-1484
FIG. 1485-1486
FIG. 1487-1488
FIG. 1489-1490
FIG. 1491-1492
FIG. 1493-1494
FIG. 1495-1496
FIG. 1497-1498
FIG. 1499-1500
FIG. 1501-1502
FIG. 1503-1504
FIG. 1505-1506
FIG. 1507-1508
FIG. 1509-1510
FIG. 1511-1512
FIG. 1513-1514
FIG. 1515-1516
FIG. 1517-1518
FIG. 1519-1520
FIG. 1521-1522
FIG. 1523-1524
FIG. 1525-1526
FIG. 1527-1528
FIG. 1529-1530
FIG. 1531-1532
FIG. 1533-1534
FIG. 1535-1536
FIG. 1537-1538
FIG. 1539-1540
FIG. 1541-1542
FIG. 1543-1544
FIG. 1545-1546
FIG. 1547-1548
FIG. 1549-1550
FIG. 1551-1552
FIG. 1553-1554
FIG. 1555-1556
FIG. 1557-1558
FIG. 1559-1560
FIG. 1561-1562
FIG. 1563-1564
FIG. 1565-1566
FIG. 1567-1568
FIG. 1569-1570
FIG. 1571-1572
FIG. 1573-1574
FIG. 1575-1576
FIG. 1577-1578
FIG. 1579-1580
FIG. 1581-1582
FIG. 1583-1584
FIG. 1585-1586
FIG. 1587-1588
FIG. 1589-1590
FIG. 1591-1592
FIG. 1593-1594
FIG. 1595-1596
FIG. 1597-1598
FIG. 1599-1600
FIG. 1601-1602
FIG. 1603-1604
FIG. 1605-1606
FIG. 1607-1608
FIG. 1609-1610
FIG. 1611-1612
FIG. 1613-1614
FIG. 1615-1616
FIG. 1617-1618
FIG. 1619-1620
FIG. 1621-1622
FIG. 1623-1624
FIG. 1625-1626
FIG. 1627-1628
FIG. 1629-1630
FIG. 1631-1632
FIG. 1633-1634
FIG. 1635-1636
FIG. 1637-1638
FIG. 1639-1640
FIG. 1641-1642
FIG. 1643-1644
FIG. 1645-1646
FIG. 1647-1648
FIG. 1649-1650
FIG. 1651-1652
FIG. 1653-1654
FIG. 1655-1656
FIG. 1657-1658
FIG. 1659-1660
FIG. 1661-1662
FIG. 1663-1664
FIG. 1665-1666
FIG. 1667-1668
FIG. 1669-1670
FIG. 1671-1672
FIG. 1673-1674
FIG. 1675-1676
FIG. 1677-1678
FIG. 1679-1680
FIG. 1681-1682
FIG. 1683-1684
FIG. 1685-1686
FIG. 1687-1688
FIG. 1689-1690
FIG. 1691-1692
FIG. 1693-1694
FIG. 1695-1696
FIG. 1697-1698
FIG. 1699-1700
FIG. 1701-1702
FIG. 1703-1704
FIG. 1705-1706
FIG. 1707-1708
FIG. 1709-1710
FIG. 1711-1712
FIG. 1713-1714
FIG. 1715-1716
FIG. 1717-1718
FIG. 1719-1720
FIG. 1721-1722
FIG. 1723-1724
FIG. 1725-1726
FIG. 1727-1728
FIG. 1729-1730
FIG. 1731-1732
FIG. 1733-1734
FIG. 1735-1736
FIG. 1737-1738
FIG. 1739-1740
FIG. 1741-1742
FIG. 1743-1744
FIG. 1745-1746
FIG. 1747-1748
FIG. 1749-1750
FIG. 1751-1752
FIG. 1753-1754
FIG. 1755-1756
FIG. 1757-1758
FIG. 1759-1760
FIG. 1761-1762
FIG. 1763-1764
FIG. 1765-1766
FIG. 1767-1768
FIG. 1769-1770
FIG. 1771-1772
FIG. 1773-1774
FIG. 1775-1776
FIG. 1777-1778
FIG. 1779-1780
FIG. 1781-1782
FIG. 1783-1784
FIG. 1785-1786
FIG. 1787-1788
FIG. 1789-1790
FIG. 1791-1792
FIG. 1793-1794
FIG. 1795-1796
FIG. 1797-1798
FIG. 1799-1800
FIG. 1801-1802
FIG. 1803-1804
FIG. 1805-1806
FIG. 1807-1808
FIG. 1809-1810
FIG. 1811-1812
FIG. 1813-1814
FIG. 1815-1816
FIG. 1817-1818
FIG. 1819-1820
FIG. 1821-1822
FIG. 1823-1824
FIG. 1825-1826
FIG. 1827-1828
FIG. 1829-1830
FIG. 1831-1832
FIG. 1833-1834
FIG. 1835-1836
FIG. 1837-1838
FIG. 1839-1840
FIG. 1841-1842
FIG. 1843-1844
FIG. 1845-1846
FIG. 1847-1848
FIG. 1849-1850
FIG. 1851-1852
FIG. 1853-1854
FIG. 1855-1856
FIG. 1857-1858
FIG. 1859-1860
FIG. 1861-1862
FIG. 1863-1864
FIG. 1865-1866
FIG. 1867-1868
FIG. 1869-1870
FIG. 1871-1872
FIG. 1873-1874
FIG. 1875-1876
FIG. 1877-1878
FIG. 1879-1880
FIG. 1881-1882
FIG. 1883-1884
FIG. 1885-1886
FIG. 1887-1888
FIG. 1889-1890
FIG. 1891-1892
FIG. 1893-1894
FIG. 189

Page 87, replace the 1st full paragraph as follows:

A15
FIG. 17
In this way, a portion of the packaging paper 782 at the distal end side forms a jutting-out portion 792 which juts out of the bundle 49. Accordingly, after the bundle is loaded into the photosensitive printing plate supplying apparatus 432 (see Fig. 17), the jutting-out portion 792 can be made jut out of the photosensitive printing plate supplying apparatus 432. The folded portions of the packaging members 782, 784 are fixed by adhesive 718H. This jutting-out portion 792 can then be pulled out. When the pulling-out force reaches a predetermined value or more, the bent portions 786 and 788 are extended and released from engagement, and the packaging member 782 can be separated from the packaging member 784.

Page 88, replace the 2nd full paragraph as follows:

A16
Namely, in the packaging paper in the eighth embodiment, the packaging members 882 and 884 are simply overlapped and the overlapped portion 894 is formed without forming the bent portions like the bent portions 786 and 788. The layers in the overlapped portion 894 are adhered to each other by an adhesive agent 896. This adhesive agent 896 effects a predetermined degree of adhesion which is strong enough to prevent packaging members 882 and 884 from being separated unnecessarily during the carrying process or the storage

A16 process but easily breaks when the predetermined value or more of the pulling-out force is applied to the packaging members 882 and 884 allowing the packaging members 882 and 884 to be separated.

Page 89, replace the 3rd paragraph as follows:

A17
F03080-ETZT2650
Further, the range which is adhered by the adhesive agent need not extend over the entire overlapped portion 816 which corresponds to the overlapped portion 416 shown in Fig. 14, and only a part of the overlapped portion may be adhered by the adhesive agent 896. For example, in the example shown in Fig. 33, only a substantially central portion of the packaging paper 810 is adhered by the adhesive agent 896. A display portion 822 is provided.

Pages 91-92, replace the bridging paragraph as follows:

A18
Consequently, the bundle 49 of the photosensitive printing plates 42 is packaged and light-shielded by the packaging paper 900. In short, the packaging paper 900 comprises a packaging paper main body 912 which packages and shields the bundle 49 of the photosensitive printing plates 42 from light and the jutting-out portions 906 which are provided at this packaging paper main body 912. A display portion 922 is provided.

Page 93, replace the 3rd full paragraph as follows:

Fig. 36 and 37 show a packaging member 1020 in a tenth embodiment of the present invention. This packaging member 1020 includes an accommodation box 1022, within which the bundle 49 of the photosensitive printing plates 42 is accommodated. The accommodation box 1022 is formed in a flat rectangular parallelepiped box shape which opens on the upper side so as to form an opening portion 1024. A display portion 1023 is provided.

Page 95, replace the 2nd full paragraph as follows:

When the bundle 49 of the photosensitive printing plates 42 which is accommodated and light-shielded in the above-structured packaging member 1020 is loaded into the photosensitive printing plate supplying apparatus 432 the jutting-out portion 1028 can be made to jut out of the photosensitive printing plate supplying apparatus 432. The jutting-out portion 1028 is then pulled out so that a portion of the photosensitive printing plate 42 can be exposed within the photosensitive printing plate supplying apparatus 432.

Page 96, replace the 2nd paragraph as follows:

A²¹
FIG. 38
FIG. 39
Figs. 38 and 39 show a packaging member 1140 in an eleventh embodiment of the present invention. This packaging member 1140 includes an accommodation box main body 1142 which has substantially the same structure as that of the accommodation box 1022 in the tenth embodiment. However, it is different in that the interior of the accommodation box main body 1142 is shielded by the light-shielding plate 1146 instead of the light-shielding paper 1026 in the tenth embodiment. A display portion 1043 is provided.

Page 97, replace the 2nd full paragraph as follows:

A²²
FIG. 40
FIG. 41
When the bundle 49 of the photosensitive printing plates 42 which is accommodated and light-shielded in the above-structured packaging member 1040 is loaded into the photosensitive printing plate supplying apparatus 432, the jutting-out portion 1150 can be made to jut out of the photosensitive printing plate supplying apparatus 432. The jutting-out portion 1150 is pulled out so that a portion of the photosensitive printing plate 42 can be exposed within the photosensitive printing plate supplying apparatus 432.